The Delphion Integrated View

Get Now: PDF | More choices... Tools: Add to Work File: Create new Wo Go to: Derwent... 🖾 Ema VI w: INPADOC | Jump to: Top

> **8**Title: JP61128459A2: SEPARATOR FOR SEALED LEAD-ACID BATTERY

JP Japan **P**Country: Α

%Kind:

SHINODA SUSUMU; PInventor:

PAssignee: **ABEKAWA SEISHI KK**

News, Profiles, Stocks and More about this company

Published / Filed: **1986-06-16** / 1984-11-28

> JP1984000249639 **P**Application

Number:

PIPC Code: H01M 2/16;

Priority Number: 1984-11-28 JP1984000249639

PAbstract:

PURPOSE: To reduce cost and increase liquid retention ability and absorbency by making a separator with the mixture of glass fibers having a mean diameter thicker than 5µm, acid resistant synthetic fibers to which hydrophobic treatment is conducted, and water-containing amorphous silica with a paper machine.

CONSTITUTION: A separator for sealed lead-acid battery is made with the mixture of 10~30wt% glass fibers having a mean diameter thicker than $5\mu m$, $40 \sim 80 \text{wt}\%$ acid resistant synthetic fibers to which hydrophobic treatment is conducted and in which at least 10wt% beating synthetic fibers are contained, 10~40wt% water-containing amorphous silica with a paper machine. Therefore, cost is reduced by removing expensive fine glass fibers, and liquid retention ability and absorbency are increased by using thicker glass fibers to increase capillary action. Moreover, by using synthetic fibers to which hydrophobic treatment is conducted, dispersion of fibers and mechanical strength are increased.

Therefore, battery performance is improved. COPYRIGHT: (C)1986, JPO& Japio

FINPADOC

None

Get Now: Family Legal Status Report

Legal Status:

Info:

Show 2 known family members **Family:**

DERABS C86-194389 DERC86-194389 **POther Abstract**



